

Becky Peak Wilderness
Legal Boundary Description

The boundary of the Becky Peak Wilderness established in the "White Pine County Conservation, Recreation, and Development Act of 2006", Public Law No. 109-432, dated December 20, 2006, Bureau of Land Management serial No. N-83920, located in Townships 23, 24, and 25 North, Range 65 East, Mount Diablo Meridian, White Pine County, in the state of Nevada, and is more particularly described as follows:

1. BEGINNING at a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, on a line parallel with and 100 feet southeasterly of the southeasterly edge of an unimproved road, bears northeasterly and southwesterly, at observed latitude 39°56'53.804" North, longitude 114°39'44.364" West; thence northeasterly turning northerly, a distance of approximately 1.5 miles, on a line parallel with and 100 feet southeasterly and easterly of the southeasterly and easterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 39°57'54.612" North, longitude 114°38'46.364" West;
2. thence northeasterly, a distance of approximately 1.2 miles, to the base of right bank of a wash, course westerly, at approximate latitude 39°58'54" North, longitude 114°38'22" West;
3. thence westerly, a distance of approximately 0.35 miles, with the meanders of the base of right bank of the wash, course westerly, to a point on said base, at approximate latitude 39°58'55" North, longitude 114°38'45" West;
4. thence northerly, a distance of approximately 0.35 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southerly of the southerly edge of an unimproved road, bears easterly and westerly, at observed latitude 39°59'13.514" North, longitude 114°38'45.067" West;
5. thence easterly, a distance of approximately 0.5 miles, on a line parallel with and 100 feet southerly of the southerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of a second unimproved road, extending southeasterly, at observed latitude 39°59'10.452" North, longitude 114°38'12.340" West;

6. thence southeasterly, a distance of approximately 0.25 miles, on a line parallel with and 100 feet southeasterly of the southeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, on said line, at observed latitude 39°59'06.426" North, longitude 114°37'58.091" West;
7. thence N. 11°38'00" E., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of the unimproved road, at observed latitude 39°59'08.458" North, longitude 114°37'57.547" West;
8. thence northwesterly, a distance of approximately 0.25 miles, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of aforementioned unimproved road, described in course No. 5, at observed latitude 39°59'12.807" North, longitude 114°38'11.921" West;
9. thence westerly, a distance of approximately 0.5 miles, on a line parallel with and 100 feet northerly of the northerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, on said line, at observed latitude 39°59'15.589" North, longitude 114°38'45.098" West;
10. thence northeasterly, a distance of approximately 0.95 mile, to a point, at approximate latitude 39°59'55.04" North, longitude 114°38'05.48" West;
11. thence northerly, a distance of approximately 1.15 miles, to a point, at approximate latitude 40°00'54.87" North, longitude 114°37'47.83" West;
12. thence northeasterly, a distance of approximately 1.2 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southerly of the southerly edge of an unimproved road, bears easterly and westerly, at observed latitude 40°01'31.712" North, longitude 114°36'42.308" West;

13. thence easterly turning southerly and northeasterly, a distance of approximately 2.6 miles, on a line parallel with and 100 feet southerly, westerly and southeasterly of the southerly, westerly and southeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet westerly of the westerly edge of a second unimproved road, bears northerly and southerly, at observed latitude 39°59'56.839" North, longitude 114°35'39.221" West;
14. thence southerly, a distance of approximately 400 feet, on a line parallel with and 100 feet westerly of the westerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet westerly of the westerly edge of a second unimproved road, bears northeasterly and southerly, at observed latitude 39°59'53.136" North, longitude 114°35'38.295" West;
15. thence southerly turning easterly, a distance of approximately 0.4 miles, on a line parallel with and 100 feet westerly and southerly of the westerly and southerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 18 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of aforementioned unimproved road, described in course No. 14, bears northeasterly and southwesterly, at observed latitude 39°59'43.275" North, longitude 114°35'27.497" West;
16. thence southwesterly, a distance of approximately 0.9 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of a second unimproved road, extending southwesterly, at observed latitude 39°59'05.191" North, longitude 114°35'47.158" West;
17. thence southwesterly, a distance of approximately 0.6 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, on said line, at observed latitude 39°58'43.904" North, longitude 114°36'13.546" West;

18. thence S. $80^{\circ}22'30''$ E., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of the unimproved road, at observed latitude $39^{\circ}58'43.557''$ North, longitude $114^{\circ}36'10.887''$ West;
19. thence northeasterly, a distance of approximately 0.55 miles, on a line parallel with and 100 feet southeasterly of the southeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 18 inches in the ground over a plastic-encased magnet, and in a mound of stone, 3 feet base, to top, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet westerly of the westerly edge of aforementioned unimproved road, described in course No. 16, bears northerly and southerly, at observed latitude $39^{\circ}59'01.484''$ North, longitude $114^{\circ}35'48.442''$ West;
20. thence southerly turning easterly, a distance of approximately 0.65 miles, on a line parallel with and 100 feet westerly, and southerly of the westerly and southerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, on said line, at observed latitude $39^{\circ}58'40.860''$ North, longitude $114^{\circ}35'40.851''$ West;
21. thence S. $3^{\circ}19'20''$ W., a distance of 209.3 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, with a collar of stones, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at observed latitude $39^{\circ}58'38.796''$ North, longitude $114^{\circ}35'41.006''$ West;
22. thence N. $87^{\circ}11'40''$ E., a distance of 566.8 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 16 inches in the ground over a plastic-encased magnet, and in a mound of stones, 3 feet base, to top, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of aforementioned unimproved road, described in course No. 20, bears northwesterly and southeasterly, at observed latitude $39^{\circ}58'39.070''$ North, longitude $114^{\circ}35'33.738''$ West;
23. thence southeasterly turning southwesterly, and southeasterly, a distance of approximately 3.5 miles, on a line parallel with and 100 feet southwesterly and northwesterly of the southwesterly and northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet

- northwesterly of the northwesterly edge of a second unimproved road, bears northeasterly and southwesterly, at observed latitude 39°56'57.249" North, longitude 114°34'05.193" West;
24. thence southwesterly, a distance of approximately 1.4 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground, over a plastic-encased magnet, and in a mound of stone, 3 feet base, to top, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of a second unimproved road, extending westerly, at observed latitude 39°56'06.769" North, longitude 114°35'05.800" West;
25. thence westerly turning northwesterly, a distance of approximately 1.55 miles, on a line parallel with and 100 feet northerly and northeasterly of the northerly and northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, on said line, at observed latitude 39°56'47.109" North, longitude 114°36'29.820" West;
26. thence S. 14°10'20" W., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road, at observed latitude 39°56'45.098" North, longitude 114°36'30.480" West;
27. thence southeasterly turning easterly, a distance of approximately 1.55 miles, on a line parallel with and 100 feet southwesterly and southerly of the southwesterly and southerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet westerly of the westerly edge of aforementioned unimproved road, described in course No. 24, bears northerly and southerly, at observed latitude 39°56'03.720" North, longitude 114°35'07.021" West;
28. thence southerly turning northwesterly and southwesterly, a distance of approximately 2.6 miles, on a line parallel with and 100 feet westerly, northwesterly and northeasterly of the westerly, northwesterly and northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground over a plastic-encased magnet, and in a mound of stone, 3 feet base, to top, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, on said line, at observed latitude 39°55'53.450" North, longitude 114°37'16.648" West;

29. thence S. $78^{\circ}16'20''$ W., a distance of 295.3 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at observed latitude $39^{\circ}55'52.857''$ North, longitude $114^{\circ}37'20.358''$ West;
30. thence S. $37^{\circ}32'40''$ W., a distance of 124.1 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at observed latitude $39^{\circ}55'51.885''$ North, longitude $114^{\circ}37'21.329''$ West;
31. thence S. $53^{\circ}48'00''$ E., a distance of 320.6 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at observed latitude $39^{\circ}55'50.013''$ North, longitude $114^{\circ}37'18.009''$ West;
32. thence N. $45^{\circ}26'40''$ E., a distance of 200.9 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of aforementioned unimproved road, described in course No. 25, bears northeasterly and southerly, at observed latitude $39^{\circ}55'51.405''$ North, longitude $114^{\circ}37'16.173''$ West;
33. thence northeasterly turning southeasterly, a distance of approximately 1.7 miles, on a line parallel with and 100 feet southeasterly and southwesterly of the southeasterly and southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of a second unimproved road, extending southeasterly at observed latitude $39^{\circ}55'31.310''$ North, longitude $114^{\circ}35'37.135''$ West;
34. thence southeasterly turning southwesterly, a distance of approximately 0.65 miles, on a line parallel with and 100 feet southwesterly and northwesterly of the southwesterly and northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of a second unimproved road, extending southwesterly, at observed latitude $39^{\circ}55'02.611''$ North, longitude $114^{\circ}35'46.662''$ West;
35. thence southwesterly turning northwesterly, a distance of approximately 1.5 miles, on a line parallel with and 100 feet

- northwesterly and northeasterly of the northwesterly and northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of a second unimproved road, bears northwesterly and southeasterly, at observed latitude 39°54'24.765" North, longitude 114°36'48.358" West;
36. thence northwesterly turning southwesterly, a distance of approximately 1.2 miles, on a line parallel with and 100 feet northeasterly and northwesterly of the northeasterly and northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, on said line, at observed latitude 39°54'46.179" North, longitude 114°37'56.578" West;
37. thence S. 20°07'40" E., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of the unimproved road, at observed latitude 39°54'44.231" North, longitude 114°37'55.651" West;
38. thence northeasterly turning southeasterly, a distance of approximately 1.55 miles, on a line parallel with and 100 feet southeasterly and southwesterly of the southeasterly and southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, on said line, at observed latitude 39°54'09.616" North, longitude 114°36'28.976" West;
39. thence southwesterly, a distance of approximately 0.95 mile, to a point, at approximate latitude 39°53'21.60" North, longitude 114°36'51.35" West;
40. thence southwesterly, a distance of approximately 0.6 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 4 inches in the ground over a plastic-encased magnet, to solid rock, and in a mound of stone, 4 feet base, to top, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of an unimproved road, bears northwesterly and southeasterly, at observed latitude 39°52'54.849" North, longitude 114°37'12.154" West;
41. thence northwesterly, a distance of approximately 1.7 miles, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the

- ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of a second unimproved road, extending northwesterly, at observed latitude 39°53'17.785" North, longitude 114°38'57.135" West;
42. thence northwesterly turning northerly, a distance of approximately 2.8 miles, on a line parallel with and 100 feet northeasterly and easterly of the northeasterly and easterly edge of the unimproved road to intersection with the east and west center line of the northeast one-quarter of section 31, T. 24 N., R. 65 E., at approximate latitude 39°55'03" North, longitude 114°40'02" West;
 43. thence easterly, a distance of approximately 0.1 mile, on the east and west center line of the northeast one-quarter of section 31, T. 24 N., R. 65 E., to the northeast one-sixteenth section corner of section 31;
 44. thence northerly, a distance of approximately 400 feet, on the north and south center line of the northeast one-quarter of section 31, T. 24 N., R. 65 E., to intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of an unimproved road, bears northwesterly and southeasterly, at approximate latitude 39°55'06" North, longitude 114°39'55" West;
 45. thence southeasterly, a distance of approximately 0.35 miles, on a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, on said line, at observed latitude 39°55'00.859" North, longitude 114°39'33.588" West;
 46. thence S. 55°00'40" E., a distance of 458.3 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stones, 2 feet base, to top, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at observed latitude 39°54'58.262" North, longitude 114°39'28.770" West;
 47. thence N. 33°01'00" E., a distance of 347.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 18 inches in the ground over a plastic-encased magnet, and in a mound of stones, 3 feet base, to top, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at observed latitude 39°55'01.137" North, longitude 114°39'26.344" West;
 48. thence N. 64°30'00" W., a distance of 136.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap

- marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of an unimproved road, bears northwesterly, at observed latitude 39°55'01.714" North, longitude 114°39'27.920" West;
49. thence northwesterly, a distance of approximately 0.1 mile, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southerly of the southerly edge of a second unimproved road, bears northeasterly and westerly, at observed latitude 39°55'06.633" North, longitude 114°39'30.853" West;
 50. thence easterly, a distance of approximately 0.4 miles, on a line parallel with and 100 feet southerly of the southerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, on said line, at observed latitude 39°55'10.166" North, longitude 114°39'07.044" West;
 51. thence N. 23°28'00" E., a distance of 210.5 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked BPW N83920 2012 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of the unimproved road, at observed latitude 39°55'12.074" North, longitude 114°39'05.968" West;
 52. thence westerly, a distance of approximately 0.8 miles, on a line parallel with and 100 feet northerly of the northerly edge of the unimproved road to intersection with the north and south center line of the southeast one-quarter of section 30, T. 24 N., R. 65 E., at approximate latitude 39°55'17" North, longitude 114°39'55" West;
 53. thence northerly, a distance of approximately 0.25 miles, on the north and south center line of the southeast one-quarter of section 30, T. 24 N., R. 65 E., to the southeast one-sixteenth section corner of section 30;
 54. thence westerly, a distance of approximately 0.25 miles, on the east and west center line of the southeast one-quarter of section 30, T. 24 N., R. 65 E., to the center south one-sixteen section corner of section 30;
 55. thence northeasterly, a distance of approximately 1.65 miles, to the base of right bank of a wash, course northwesterly, at approximate latitude 39°56'50" North, longitude 114°39'34" West;

56. thence northwesterly, a distance of approximately 0.15 miles, with the meanders of the base of the right bank of the wash, course northwesterly, to the Point of Beginning.

The area contained within the bounds of this description is 18,190 acres, more or less.

END OF DESCRIPTION

The acreage noted in the description is based on a GIS polygon projected onto the 1983 North American Datum Universal Transverse Mercator projection, zone 11.

The direction of each line is with reference to the true meridian.

The geographic positions noted as "approximate" latitude and longitude are referenced to the North American Datum of 1983 and were digitized from the following editions of the United States Geologic Survey 7.5 minute quadrangle maps:

Cherry Spring, Nev., Provisional Edition, 1982
 Becky Peak, Nev., Provisional Edition, 1982
 Goshute Lake South, Nev., Provisional Edition, 1982
 Lages Station, Nev., 1982

The geographic positions noted as "observed" latitude and longitude are referenced to the North American Datum of 1983. Observed positions were determined in 2012 and 2013 utilizing Global Positioning System (GPS), Real Time Kinematic (RTK) observations. All RTK observations were carried forward from local control established using GPS static observations processed with the National Geodetic Survey Online Positioning User Service (OPUS) referenced to the following Continuously Operating Reference Stations (CORS):

"EGAN EGAN BRGN NV1996 CORS ARP"
 "GOSH GOSH BRGN UT1996 CORS ARP"
 "NVPI PIOCHE CORS ARP"
 "LKN1 ELKO CORS ARP"
 "P113 KNOLLSWEST UT2006 CORS ARP"
 "SPRING VALLEY CORS ARP".

WILDERNESS AREA
Becky Peak Wilderness
Bureau of Land Management

I hereby certify that the maps and legal boundary description herewith represents the boundary of the Becky Peak Wilderness within the jurisdiction of the Ely District Office, Nevada, Bureau of Land Management.

Signed: _____ Date: _____
Chief, Branch of Geographic Sciences
Bureau of Land Management, Nevada

I hereby certify and accept the maps and legal boundary description of Becky Peak Wilderness within the Ely District Office, Nevada, Bureau of Land Management, as entered into the Wilderness System under the "White Pine County Conservation, Recreation, and Development Act of 2006", Public Law No. 109-432, dated December 20, 2006.

Signed: _____ Date: _____
State Director, Nevada
Bureau of Land Management