

Mount Grafton Wilderness

Legal Boundary Description

The boundary of the Mount Grafton Wilderness established in the "White Pine County Conservation, Recreation, and Development Act of 2006", Public Law No. 109-432, dated December 20, 2006, Bureau of Land Management Serial No. N-83916, located in Townships 9 North, Ranges 64 and 65 East, Townships 10 North, Ranges 63, 64, and 65 East, and Townships 11 North, Ranges 64 and 65 East, Mount Diablo Meridian, White Pine and Lincoln Counties, in the state of Nevada, is more particularly described as follows:

1. BEGINNING at the corner of sections 5, 6, 31, and 32, on the north boundary of T. 11 N., R. 64 E., monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above the ground, with brass cap marked T12N R64E S31 S32 S5 S6 T11N 1964, with a mound of stone, 3 feet diameter, 6 inches high, westerly of the corner, at observed latitude 38°51'01.617" North, longitude 114°49'07.391" West; thence easterly, a distance of approximately 1.0 mile, on the line between sections 5 and 32, and on the north boundary of T. 11 N., R. 64 E., to the corner of sections 4, 5, 32, and 33;
2. thence southerly, a distance of approximately 0.75 miles, on the line between sections 4 and 5, T. 11 N., R. 64 E., to the south one-sixteenth section corner of sections 4 and 5;
3. thence easterly, a distance of approximately 0.5 miles, on the east and west center line of the southwest one-quarter of section 4, T. 11 N., R. 64 E., to the center south one-sixteenth section corner of section 4;
4. thence southerly, a distance of approximately 0.25 miles, on the north and south center line of section 4, T. 11 N., R. 64 E., to the one-quarter section corner of sections 4 and 9;
5. thence southerly, a distance of approximately 0.5 miles, to a spur, slopes northeasterly, at approximate latitude 38°49'45" North, longitude 114°47'22" West;
6. thence southeasterly, a distance of approximately 0.85 miles, to a point, at approximate latitude 38°49'02.29" North, longitude 114°47'03.06" West;
7. thence southerly, a distance of approximately 1.15 miles, to a point, at approximate latitude 38°48'01.74" North, longitude 114°47'03.00" West;
8. thence southeasterly, a distance of approximately 0.45 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of a jeep trail, bears northeasterly and southwesterly, at observed latitude 38°47'42.105" North, longitude 114°46'48.829" West;

9. thence southwesterly turning southeasterly and northeasterly, a distance of approximately 0.75 miles, on a line parallel with and 100 feet northwesterly, southwesterly and southeasterly of the northwesterly, southwesterly, and southeasterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of a second unimproved road, at observed latitude 38°47'32.007" North, longitude 114°46'21.720" West;
10. thence southeasterly turning northeasterly and southeasterly, a distance of approximately 2.7 miles, on a line parallel with and 100 feet southwesterly, southeasterly and southwesterly of the southwesterly, southeasterly and southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with a collar of stone, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 38°45'53.477" North, longitude 114°45'08.027" West;
11. thence N. 59°10'30" E., a distance of 441.8 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with a collar of stone, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°45'55.714" North, longitude 114°45'03.239" West;
12. thence N. 57°51'00" W., a distance of 268.6 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°45'57.126" North, longitude 114°45'06.109" West;
13. thence S. 53°56'50" W., a distance of 137.6 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of aforementioned unimproved road, described in course No. 10, at observed latitude 38°45'56.325" North, longitude 114°45'07.514" West;
14. thence northwesterly turning southwesterly, northwesterly, and northerly, a distance of approximately 4.3 miles, on a line parallel with and 100 feet northeasterly, northwesterly, and easterly of the northeasterly, northwesterly, and easterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of a second unimproved road, bears

- southeasterly and northwesterly, at observed latitude 38°48'55.639 North, longitude 114°46'07.437" West;
15. thence southeasterly turning southwesterly, a distance of approximately 3.3 miles, on a line parallel with and 100 feet southwesterly and northwesterly of the southwesterly and northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 38°47'06.061" North, longitude 114°43'54.983" West;
 16. thence S. 58°22'00" E., a distance of 210.7 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, with a collar of stone, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of the unimproved road, at observed latitude 38°47'04.970" North, longitude 114°43'52.719" West;
 17. thence northeasterly turning northwesterly, a distance of approximately 3.4 miles, on a line parallel with and 100 feet southeasterly and northeasterly of the southeasterly and northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with a collar of stone, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 38°48'57.944" North, longitude 114°46'06.782" West;
 18. thence northeasterly, a distance of approximately 0.7 miles, to a knoll, at approximate latitude 38°49'25" North, longitude 114°45'34" West;
 19. thence southeasterly, a distance of approximately 0.55 miles, to a knoll, at approximate elevation of 7,565 feet and approximate latitude 38°49'16" North, longitude 114°44'59" West;
 20. thence southeasterly, a distance of approximately 0.85 miles, to a knoll, at approximate latitude 38°48'59" North, longitude 114°44'08" West;
 21. thence northeasterly, a distance of approximately 0.35 miles, to a knoll, at approximate latitude 38°49'09" North, longitude 114°43'49" West;
 22. thence northerly, a distance of approximately 0.2 miles, to the east one-sixteenth section corner of sections 12 and 13, T. 11 N., R. 64 E.;
 23. thence northerly, a distance of approximately 150 feet, on the north and south center line of the southeast one-quarter of section 12, T. 11 N., R. 64 E., to a line parallel with and approximately 50 feet southerly of a fence line, bears easterly

and westerly, at approximate latitude 38°49'22" North, longitude 114°43'50" West;

24. thence easterly turning southeasterly and northeasterly, a distance of approximately 0.95 mile, on a line parallel with and 50 feet southerly, southwesterly, and southeasterly of a fence line to intersection with the east and west center line of the southeast one-quarter of section 7, T. 11 N., R. 65 E., at approximate latitude 38°49'34" North, longitude 114°42'54" West;
25. thence easterly, a distance of approximately 0.15 miles, on the east and west center line of the southeast one-quarter of section 7, T. 11 N., R. 65 E., to the southeast one-sixteenth section corner of section 7;
26. thence northerly, a distance of approximately 150 feet, on the north and south center line of the southeast one-quarter of section 7, T. 11 N., R. 65 E., to intersection with a line parallel with and 50 feet southerly of the aforementioned fence line, bears northeasterly and southwesterly, at approximate latitude 38°49'35" North, longitude 114°42'44" West;
27. thence northeasterly, a distance of approximately 0.40 miles, on a line parallel with and 50 feet southeasterly of the aforementioned fence line to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of an unimproved road, bears northeasterly and southwesterly, at observed latitude 38°49'42.722" North, longitude 114°42'19.210" West;
28. thence southwesterly turning southeasterly and southwesterly, a distance of approximately 2.3 miles, on a line parallel with and 100 feet northwesterly, southwesterly and northwesterly of the northwesterly, southwesterly and northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 38°48'09.860" North, longitude 114°41'26.421" West;
29. thence N. 63°20'30" W., a distance of 225.1 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with a collar of stone, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°48'10.858" North, longitude 114°41'28.961" West;
30. thence S. 36°09'50" W., a distance of 201.1 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 15 inches in the ground over a plastic-encased magnet, to solid rock, and in a mound of stone, 3 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°48'09.254" North, longitude

114°41'30.459" West;

31. thence S. 38°39'50" E., a distance of 178.8 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of aforementioned unimproved road, bears northeasterly and southwesterly, at observed latitude 38°48'07.875" North, longitude 114°41'29.049" West;
32. thence southerly turning southeasterly, a distance of approximately 6.1 miles, on a line parallel with and 100 feet westerly and southwesterly of the westerly and southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with a collar of stone, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 38°44'07.661" North, longitude 114°40'07.261" West;
33. thence S. 52°43'00" W., a distance of 362.2 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°44'05.492" North, longitude 114°40'10.897" West;
34. thence S. 35°40'30" E., a distance of 726.3 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°43'59.662" North, longitude 114°40'05.553" West;
35. thence N. 50°54'50" E., a distance of 452.1 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of the aforementioned unimproved road, described in course No. 32, bears northwesterly and southeasterly, at observed latitude 38°44'02.479" North, longitude 114°40'01.126" West;
36. thence southeasterly, a distance of approximately 1.1 miles, on a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of a second unimproved road, bears northeasterly and southwesterly, at observed latitude 38°43'28.752" North, longitude 114°39'01.251" West;

37. thence southerly, a distance of approximately 1.7 miles, on a line parallel with and 100 feet westerly of the westerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of a second unimproved road, bears northwesterly and southeasterly, at observed latitude 38°42'02.122" North, longitude 114°39'07.286" West;
38. thence northwesterly turning westerly, a distance of approximately 4.5 miles, on a line parallel with and 100 feet northeasterly and northerly of the northeasterly and northerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 38°43'52.645" North, longitude 114°42'48.582" West;
39. thence N. 11°44'00" E., a distance of 129.4 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, in a mound of stone, 2 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°43'53.898" North, longitude 114°42'48.250" West;
40. thence N. 61°07'00" W., a distance of 517.9 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, in a mound of stone, 3 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°43'56.369" North, longitude 114°42'53.970" West;
41. thence S. 87°26'40" W., a distance of 160.2 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground over a plastic-encased magnet, to solid rock, and in a mound of stone, 3 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°43'56.299" North, longitude 114°42'55.989" West;
42. thence S. 3°37'20" W., a distance of 301.8 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 28 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southerly of the southerly edge of the unimproved road, at observed latitude 38°43'53.322" North, longitude 114°42'56.230" West;
43. thence easterly turning southeasterly, a distance of approximately 4.6 miles, on a line parallel with and 100 feet southerly and southwesterly of the southerly and southwesterly edge of unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 28 inches in the ground over a

plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of a second unimproved road, bears easterly and westerly, at observed latitude $38^{\circ}41'58.787''$ North, longitude $114^{\circ}39'07.903''$ West;

44. thence westerly, a distance of approximately 1.8 miles, on a line parallel with and 100 feet northerly of the northerly edge of unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 28 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, at observed latitude $38^{\circ}42'10.238''$ North, longitude $114^{\circ}40'58.698''$ West;
45. thence S. $30^{\circ}16'00''$ E., a distance of 220.0 feet, crossing the aforementioned unimproved road described in course No. 44, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 28 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of an unimproved road, bears northwesterly and southeasterly, at observed latitude $38^{\circ}42'08.361''$ North, longitude $114^{\circ}40'57.300''$ West;
46. thence southeasterly, a distance of approximately 2.0 miles, on a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet westerly of the westerly edge of a second unimproved road, bears northerly and southerly, at observed latitude $38^{\circ}41'17.294''$ North, longitude $114^{\circ}39'07.219''$ West;
47. thence southerly, a distance of approximately 0.8 miles, on a line parallel with and 100 feet westerly of the westerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 28 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of a second unimproved road, bears easterly and westerly, at observed latitude $38^{\circ}40'36.155''$ North, longitude $114^{\circ}39'11.433''$ West;
48. thence westerly turning northerly, a distance of approximately 0.9 miles, on a line parallel with and 100 feet northerly and easterly of the northerly and easterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 15 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, and in a mound of stone, 4 feet base, to top, at observed latitude $38^{\circ}40'42.245''$ North, longitude $114^{\circ}39'47.884''$ West;

49. thence N. 2°06'30" E., a distance of 573.4 feet, to a stainless steel post, 26 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with a collar of stone, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°40'47.908" North, longitude 114°39'47.618" West;
50. thence N. 84°07'00" W., a distance of 916.7 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, and in a mound of stone, 2 feet base, to top, at observed latitude 38°40'48.833" North, longitude 114°39'59.114" West;
51. thence S. 79°18'30" W., a distance of 260.1 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, with a mound of stone, 2 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°40'48.356" North, longitude 114°40'02.336" West;
52. thence S. 17°37'50" E., a distance of 200.4 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, located near terminus of unimproved road, at observed latitude 38°40'46.469" North, longitude 114°40'01.571" West;
53. thence S. 86°43'50" E., a distance of 781.3 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southerly of the southerly edge of the aforementioned unimproved road, described in course No. 42, bears westerly and southerly, at observed latitude 38°40'46.029" North, longitude 114°39'51.738" West;
54. thence southerly and turning easterly, a distance of approximately 1.6 miles, on a line parallel with and 100 feet westerly and southerly of the westerly and southerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°40'35.764" North, longitude 114°38'31.356" West;
55. thence southerly, a distance of approximately 0.4 miles, to a point, at approximate latitude 38°40'16.00" North, longitude 114°38'32.87" West;
56. thence southerly, a distance of approximately 0.4 miles, to a point, at approximate latitude 38°39'55.63" North, longitude 114°38'37.15" West;

57. thence southerly, a distance of approximately 0.4 miles, to a point, at approximate latitude $38^{\circ}39'33.93''$ North, longitude $114^{\circ}38'40.16''$ West;
58. thence southerly, a distance of approximately 0.5 miles, to a point, at approximate latitude $38^{\circ}39'08.70''$ North, longitude $114^{\circ}38'47.80''$ West;
59. thence southerly, a distance of approximately 0.15 mile, to a brass tablet, 3 1/4 inch diameter, 3 1/2 inch stem, cemented in a drill hole of solid rock, with top marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of an unimproved road, extending southerly at observed latitude $38^{\circ}39'01.678''$ North, longitude $114^{\circ}38'47.505''$ West;
60. thence southerly, a distance of approximately 0.2 miles, on a line parallel with and 100 feet westerly of the westerly edge of unimproved road to intersection with the line between sections 11 and 14, T. 9 N., R. 65 E., at approximate latitude $38^{\circ}38'53''$ North, longitude $114^{\circ}38'48''$ West;
61. thence westerly, a distance of approximately 300 feet, on the line between sections 11 and 14, T. 9 N., R. 65 E., to the one-quarter section corner of sections 11 and 14;
62. thence southerly, a distance of approximately 0.2 miles, on the north and south center line of section 14, T. 9 N., R. 65 E., to intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of an unimproved road, at approximate latitude $38^{\circ}38'43''$ North, longitude $114^{\circ}38'52''$ West;
63. thence westerly, a distance of approximately 120 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude $38^{\circ}38'43.314''$ North, longitude $114^{\circ}38'53.642''$ West;
64. thence S. $1^{\circ}18'10''$ E., a distance of 178.2 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude $38^{\circ}38'41.554''$ North, longitude $114^{\circ}38'53.591''$ West;
65. thence southwesterly, a distance of approximately 0.15 miles, to a point, at approximate latitude $38^{\circ}38'34.57''$ North, longitude $114^{\circ}38'57.30''$ West;
66. thence southerly, a distance of approximately 0.35 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 14 inches in the ground over a plastic-encased magnet, to solid rock, and in a mound of stone, 3 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of

- the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of an unimproved road, bears northwesterly and southeasterly, at observed latitude 38°38'16.245" North, longitude 114°38'59.267" West;
67. thence northwesterly, a distance of approximately 1.4 miles, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 38°38'39.087" North, longitude 114°40'25.594" West;
68. thence S. 29°31'00" W., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road, at observed latitude 38°38'37.281" North, longitude 114°40'26.898" West;
69. thence southeasterly, a distance of approximately 1.4 miles, on a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 38°38'14.242" North, longitude 114°39'00.026" West;
70. thence southwesterly, a distance of approximately 0.3 miles, to a point, at approximate latitude 38°37'59.21" North, longitude 114°39'05.87" West;
71. thence southerly, a distance of approximately 0.25 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 14 inches in the ground over a plastic-encased magnet, to solid rock, and in a mound of stone, 3 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southerly of the southerly edge of an unimproved road, bears easterly and westerly, at observed latitude 38°37'46.671" North, longitude 114°39'09.756" West;
72. thence easterly, a distance of approximately 0.15 miles, on a line parallel with and 100 feet southerly of the southerly edge of unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with a collar of stone, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of a second unimproved road, bears northeasterly and southwesterly, at observed latitude 38°37'45.367" North, longitude 114°39'00.730" West;

73. thence southwesterly, a distance of approximately 2.5 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with a collar of stone, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of a second unimproved road, bears northerly and southeasterly, at observed latitude 38°36'09.440" North, longitude 114°40'51.122" West;
74. thence northerly turning northwesterly, a distance of approximately 1.6 miles, on a line parallel with and 100 feet easterly and northeasterly of the easterly and northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet westerly of the westerly edge of a second unimproved road, bears northerly and southerly, at observed latitude 38°36'47.633" North, longitude 114°42'14.576" West;
75. thence southerly, a distance of approximately 0.4 miles, on a line parallel with and 100 feet westerly of the westerly edge of the second unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with a collar of stone, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at the base of right bank of a wash, course easterly, at observed latitude 38°36'28.482" North, longitude 114°42'05.250" West;
76. thence westerly, a distance of approximately 0.13 mile, with the meanders of the base of right bank of the wash, course easterly, to a point at approximate latitude 38°36'29" North, longitude 114°42'13" West;
77. thence southerly, a distance of approximately 0.4 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on the base of left bank of a wash, course easterly, at observed latitude 38°36'08.367" North, longitude 114°42'05.939" West;
78. thence westerly, a distance of approximately 0.7 miles, with the meanders of the base of left bank of a wash, course easterly, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of a jeep trail, bears northwesterly and southeasterly, at observed latitude 38°36'06.797" North, longitude 114°42'51.512" West;
79. thence northwesterly turning northerly, a distance of

- approximately 2.3 miles, on a line parallel with and 100 feet northeasterly and easterly of the northeasterly and easterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 12 inches in the ground over a plastic-encased magnet, to solid rock, and in a mound of stone, 4 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a second jeep trail, bears northeasterly, at observed latitude 38°37'27.335" North, longitude 114°43'31.639" West;
80. thence northeasterly turning westerly, a distance of approximately 0.4 miles, on a line parallel with and 100 feet southeasterly and northerly of the southeasterly and northerly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of aforementioned jeep trail, described in course No. 79, bears northwesterly and southwesterly, at observed latitude 38°37'32.948" North, longitude 114°43'36.144" West;
81. thence northwesterly turning southwesterly, a distance of approximately 0.25 miles, on a line parallel with and 100 feet northeasterly and northwesterly of the northeasterly and northwesterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, with a collar of stone, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°37'29.376" North, longitude 114°43'46.955" West;
82. thence southwesterly, a distance of approximately 0.75 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the jeep trail, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, in a mound of stone, 3 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 38°36'59.380" North, longitude 114°44'13.653" West;
83. thence southwesterly, a distance of approximately 250 feet, to a saddle, bears easterly and westerly, at approximate latitude 38°36'58" North, longitude 114°44'16" West;
84. thence northwesterly, a distance of approximately 250 feet, to the base of right bank of wash, course northwesterly, at approximate latitude 38°37'00" North, longitude 114°44'18" West;
85. thence northwesterly, a distance of approximately 0.15 miles, with the meanders of the base of right bank of the wash, course northwesterly, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, with a collar of stone, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet

- northeasterly of the northeasterly edge of a jeep trail, bears northwesterly and southwesterly, at observed latitude 38°37'08.463" North, longitude 114°44'22.167" West;
86. thence northwesterly turning southerly, a distance of approximately 1.8 miles, on a line parallel with and 100 feet northeasterly and westerly of the northeasterly and westerly edge of jeep trail to a point on said line, at approximate latitude 38°36'19.1" North, longitude 114°45'13.8" West;
 87. thence southeasterly, a distance of approximately 0.25 miles, to a spur, slopes southerly, at approximate latitude 38°36'08" North, longitude 114°45'05" West;
 88. thence southwesterly, a distance of approximately 0.55 miles, to a point, at approximate latitude 38°35'43.04" North, longitude 114°45'22.22" West;
 89. thence southeasterly, a distance of approximately 0.55 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, in a mound of stone, 3 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary to intersection with a line parallel with and 100 feet northerly of the northerly edge of an improved road, bears easterly and westerly, at observed latitude 38°35'17.933" North, longitude 114°45'07.666" West;
 90. thence westerly turning northwesterly, a distance of approximately 1.1 miles, on a line parallel with and 100 feet northerly and northeasterly of the northerly and northeasterly edge of the improved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, in a mound of stone, 2 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of a second improved road, bears northeasterly and southwesterly, at observed latitude 38°35'37.570" North, longitude 114°46'13.648" West;
 91. thence northeasterly turning northwesterly, a distance of approximately 0.3 miles, on a line parallel with and 100 feet southeasterly and northeasterly of the southeasterly and northeasterly edge of an improved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 26 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at the centerline of a second improved road, bears northeasterly and southwesterly, at observed latitude 38°35'52.542" North, longitude 114°46'16.650" West;
 92. thence northwesterly, a distance of approximately 0.7 miles, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the improved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW

- N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of an unimproved road, bears northeasterly and southwesterly, at observed latitude $38^{\circ}36'20.255''$ North, longitude $114^{\circ}46'47.150''$ West;
93. thence northeasterly, a distance of approximately 1.6 miles, on a line parallel with and 100 feet southeasterly of the southeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 26 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, at observed latitude $38^{\circ}36'50.718''$ North, longitude $114^{\circ}45'19.853''$ West;
94. thence S. $89^{\circ}22'20''$ E., a distance of 314.3 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 28 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude $38^{\circ}36'50.684''$ North, longitude $114^{\circ}45'15.896''$ West;
95. thence N. $10^{\circ}24'40''$ W., a distance of 386.3 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 3 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude $38^{\circ}36'54.438''$ North, longitude $114^{\circ}45'16.775''$ West;
96. thence S. $64^{\circ}57'10''$ W., a distance of 241.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 26 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of the aforementioned unimproved road, described in course No. 93, bears northeasterly and southwesterly, at observed latitude $38^{\circ}36'53.430''$ North, longitude $114^{\circ}45'19.524''$ West;
97. thence southwesterly, a distance of approximately 1.6 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of the aforementioned improved road, described in course No. 92, bears northwesterly and southeasterly, at observed latitude $38^{\circ}36'21.905''$ North, longitude $114^{\circ}46'48.803''$ West;
98. thence northwesterly, a distance of approximately 1.95 miles, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the improved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary,

- at intersection with a line parallel with and 100 feet southerly of the southerly edge of an unimproved road, bears easterly and westerly, at observed latitude $38^{\circ}37'47.425''$ North, longitude $114^{\circ}47'57.909''$ West;
99. thence easterly, a distance of approximately 0.6 miles, on a line parallel with and 100 feet southerly of the southerly edge of the unimproved road to intersection with the line between sections 21 and 22, Township 9 North, Range 64 E., at approximate latitude $38^{\circ}37'48''$ North, longitude $114^{\circ}47'17''$ West;
100. thence northerly, a distance of approximately 100 feet, to the corner of sections 15, 16, 21, and 22, T. 9 N., R. 64 E., at approximate latitude $38^{\circ}37'49''$ North, longitude $114^{\circ}47'17''$ West;
101. thence northerly, a distance of approximately 0.25 miles, on the line between sections 15 and 16, T. 9 N., R. 64 E., to the south one-sixteenth section corner of sections 15 and 16;
102. thence easterly, a distance of approximately 0.25 miles, on the east and west center line of the southwest one-quarter of section 15, T. 9 N., R. 64 E., to the southwest one-sixteenth section corner of section 15;
103. thence northerly, a distance of approximately 0.25 miles, on the north and south center line of the southwest one-quarter of section 15, T. 9 N., R. 64 E., to the center-west, one-sixteenth section corner of section 15;
104. thence northerly, a distance of approximately 0.25 miles, on the north and south center line of the northwest one-quarter of section 15, T. 9 N., R. 64 E., to the northwest one-sixteenth section corner of section 15;
105. thence westerly, a distance of approximately 400 feet, on the east and west center line of the northwest one-quarter of section 15, T. 9 N., R. 64 E., to intersection with a line parallel with and 100 feet easterly of the easterly edge of a jeep trail, bears northerly and southerly, at approximate latitude $38^{\circ}38'29''$ North, longitude $114^{\circ}47'06''$ West;
106. thence northerly, a distance of approximately 0.2 miles, on a line parallel with and 100 feet easterly of the easterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, in a collar of stone, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of a second jeep trail, bears easterly and westerly, at observed latitude $38^{\circ}38'39.721''$ North, longitude $114^{\circ}47'07.393''$ West;
107. thence westerly, a distance of approximately 0.9 miles, on a line parallel with and 100 feet northerly of the northerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, in a collar of stone, with brass cap marked MGW

N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°38'50.496" North, longitude 114°48'04.946" West;

108. thence northwesterly, a distance of approximately 500 feet, to the southwest one-sixteenth section corner of section 9, T. 9 N., R. 64 E.;
109. thence northerly, a distance of approximately 0.25 miles, on the north and south center line of the southwest one-quarter of section 9, T. 9 N., R. 64 E., to the center-west, one-sixteenth section corner of section 9;
110. thence northerly, a distance of approximately 0.5 miles, on the north and south center line of the northwest one-quarter of section 9, T. 9 N., R. 64 E., to the west one-sixteenth section corner of sections 4 and 9;
111. thence northerly, a distance of approximately 0.25 miles, on the north and south center line of the southwest one-quarter of section 4, T. 9 N., R. 64 E., to the southwest one-sixteenth section corner of section 4;
112. thence westerly, a distance of approximately 0.25 miles, on the east and west center line of the southwest one-quarter of section 4, T. 9 N., R. 64 E., to the south one-sixteenth section corner of sections 4 and 5;
113. thence westerly, a distance of approximately 0.5 miles, on the east and west center line of the southeast one-quarter of section 5, T. 9 N., R. 64 E., to the center-south, one-sixteenth section corner of section 5;
114. thence northerly, a distance of approximately 450 feet, on the north and south center line of section 5, T. 9 N., R. 64 E. to a point, at approximate latitude 38°39'52.0" North, longitude 114°48'57" West;
115. thence southwesterly, a distance of approximately 200 feet, to intersection with a line 100 feet northwesterly of the northwesterly edge of an unimproved road at approximate latitude 38°39'51" North, longitude 114°48'59" West;
116. thence southwesterly, a distance of approximately 0.1 mile on a line parallel with and 100 feet northwesterly of the northwesterly edge of the unimproved road to intersection with the east and west center line of the southwest one-quarter of section 5, T. 9 N., R. 64 E. at approximate latitude 38°39'47" North, longitude 114°49'06" West;
117. thence westerly, a distance of approximately 600 feet, on the east and west center line of the southwest one-quarter of section 5, T. 9 N., R. 64 E., to the southwest one-sixteenth section corner of section 5;
118. thence southerly, a distance of approximately 500 feet on the north and south center line of the southwest one-quarter of

- section 5, T. 9 N., R. 64 E., to intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of the aforementioned unimproved road, at approximate latitude 38°39'42" North, longitude 114°49'13" West;
119. thence southwesterly, a distance of approximately 0.2 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground over a plastic-encased magnet, in a mound of stone, 2 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of an improved road, at observed latitude 38°39'36.472" North, longitude 114°49'23.967" West;
120. thence northwesterly, a distance of approximately 0.6 miles, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the improved road to intersection with the north and south center line of the northeast one-quarter of section 6, T. 9 N., R. 64 E., at approximate latitude 38°40'01" North, longitude 114°49'46" West;
121. thence northerly, a distance of approximately 0.3 miles, on the north and south center line of the northeast one-quarter of section 6, T. 9 N., R. 64 E., to intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of an unimproved road, bears northeasterly and southwesterly, at approximate latitude 38°40'17" North, longitude 114°49'46" West;
122. thence northeasterly, a distance of approximately 0.45 miles, on a line parallel with and 100 feet southeasterly of the southeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 38°40'39.402" North, longitude 114°49'35.219" West;
123. thence N. 73°05'10" E., a distance of 117.7 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, in a mound of stone, 2 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°40'39.741" North, longitude 114°49'33.800" West;
124. thence N. 43°03'50" E., a distance of 256.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, in a mound of stone, 2 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°40'41.589" North, longitude 114°49'31.596" West;
125. thence N. 37°53'00" W., a distance of 54.9 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, in a mound of stone,

- 2 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of aforementioned unimproved road, described in course No. 122, at observed latitude $38^{\circ}40'42.017''$ North, longitude $114^{\circ}49'32.021''$ West;
126. thence northeasterly, a distance of approximately 0.85 miles, on a line parallel with and 100 feet southeasterly of the southeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground over a plastic-encased magnet, in a mound of stone, 2 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, at observed latitude $38^{\circ}41'17.788''$ North, longitude $114^{\circ}49'03.730''$ West;
127. thence S. $56^{\circ}51'10''$ E., a distance of 1,003.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground over a plastic-encased magnet, in a mound of stone, 2 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude $38^{\circ}41'12.369''$ North, longitude $114^{\circ}48'53.143''$ West;
128. thence N. $33^{\circ}08'10''$ E., a distance of 464.6 feet, to a brass tablet, 3 1/4 inch diameter, 3 1/2 inch stem, cemented in a drill hole in solid rock, with top marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude $38^{\circ}41'16.214''$ North, longitude $114^{\circ}48'49.941''$ West;
129. thence N. $57^{\circ}20'30''$ W., a distance of 636.7 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with a collar of stone, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude $38^{\circ}41'19.609''$ North, longitude $114^{\circ}48'56.700''$ West;
130. thence S. $76^{\circ}55'00''$ W., a distance of 333.8 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with a collar of stone, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of aforementioned unimproved road, at observed latitude $38^{\circ}41'18.862''$ North, longitude $114^{\circ}49'00.799''$ West;
131. thence northeasterly, a distance of approximately 1.35 miles, on a line parallel with and 100 feet southeasterly of the southeasterly edge of the aforementioned unimproved road, to intersection with the north and south center line of section 28, T. 10 N., R. 64 E., at approximate latitude $38^{\circ}41'58''$ North, longitude $114^{\circ}47'49''$ West;
132. thence southerly, a distance of approximately 0.2 miles, on the north and south center line of section 28, T. 10 N., R. 64 E., to the center one-quarter section corner of section 28;

133. thence easterly, a distance of approximately 0.5 miles, on the east and west center line of section 28, T. 10 N., R. 64 E., to the one-quarter section corner of sections 27 and 28;
134. thence easterly, a distance of approximately 1.0 mile, on the east and west center line of section 27, T. 10 N., R. 64 E., to the one-quarter section corner of sections 26 and 27;
135. thence easterly, a distance of approximately 0.25 miles, on the east and west center line of section 26, T. 10 N., R. 64 E., to the west one-sixteenth section corner of section 26;
136. thence northerly, a distance of approximately 0.25 miles, on the north and south center line of the northwest one-quarter of section 26, T. 10 N., R. 64 E., to the northwest one-sixteenth section corner of section 26;
137. thence westerly, a distance of approximately 0.25 miles, on the east and west center line of the northwest one-quarter of section 26, T. 10 N., R. 64 E., to the north one-sixteenth section corner of sections 26 and 27;
138. thence westerly, a distance of approximately 0.25 miles, on the east and west center line of the northeast one-quarter of section 27, T. 10 N., R. 64 E., to the northeast one-sixteenth section corner of section 27;
139. thence northerly, a distance of approximately 0.25 miles, on the north and south center line of the northeast one-quarter of section 27, T. 10 N., R. 64 E., to the east one-sixteenth section corner of sections 22 and 27;
140. thence westerly, a distance of approximately 0.25 miles, on the line between sections 22 and 27, T. 10 N., R. 64 E., to the one-quarter section corner of sections 22 and 27;
141. thence southerly, a distance of approximately 0.15 miles, on the north and south center line of section 27, T. 10 N., R. 64 E., to intersection with a line parallel with and 100 feet northerly of the northerly edge of the aforementioned unimproved road, described in course No. 131, bears easterly and westerly;
142. thence westerly turning southwesterly, a distance of approximately 3.7 miles, on a line parallel with and 100 feet northerly and northwesterly of the northerly and northwesterly edge of the unimproved road to intersection with the north and south center line of the northeast one-quarter of section 6, T. 9 N., R. 64 E., at approximate latitude $38^{\circ}40'24''$ North, longitude $114^{\circ}49'46''$ West;
143. thence northerly, a distance of approximately 300 feet, on the north and south center line of the northeast one-quarter of section 6, T. 9 N., R. 64 E., to the line between sections 6 and 31, on the north boundary of T. 9 N., R. 64 E.;
144. thence westerly, a distance of approximately 0.25 miles, on the

- line between sections 6 and 31, on the north boundary of T. 9 N., R. 64 E., to intersection with a line parallel with and 100 feet northeasterly of the northwesterly edge of the aforementioned improved road, described in course No. 120, at approximate latitude $38^{\circ}40'27''$ North, longitude $114^{\circ}50'02''$ West;
145. thence northwesterly, a distance of approximately 60 feet, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the improved road, to intersection with the north and south center line of section 31, T. 10 N., R. 64 E., at approximate latitude $38^{\circ}40'28''$ North, longitude $114^{\circ}50'03''$ West;
146. thence northerly, a distance of approximately 0.5 miles, on the north and south center line of section 31, T. 10 N., R. 64 E., to the center one-quarter section corner of section 31;
147. thence westerly, a distance of approximately 0.2 miles, on the east and west center line of section 31, T. 10 N., R. 64 E., to intersection with a line parallel with and 100 feet easterly of the easterly edge of the aforementioned unimproved road, described in course No. 145, bears southwesterly and northerly, at approximate latitude $38^{\circ}40'54''$ North, longitude $114^{\circ}50'17''$ West;
148. thence northerly, a distance of approximately 0.5 miles, on a line parallel with and 100 feet easterly of the easterly edge of the improved road to intersection with the north and south center line of the northwest one-quarter of section 31, T. 10 N., R. 64 E.;
149. thence northerly, a distance of approximately 250 feet, on the north and south center line of the northwest one-quarter of section 31, T. 10 N., R. 64 E., to the west one-sixteenth section corner of sections 30 and 31;
150. thence northerly, a distance of approximately 0.5 miles, on the north and south center line of the southwest one-quarter of section 30, T. 10 N., R. 64 E., to the center-west, one-sixteenth section corner of section 30;
151. thence northerly, a distance of approximately 0.5 miles, on the north and south center line of the northwest one-quarter of section 30, T. 10 N., R. 64 E., to the west one-sixteenth section corner of sections 19 and 30;
152. thence northerly, a distance of approximately 0.5 miles, on the north and south center line of the southwest one-quarter of section 19, T. 10 N., R. 64 E., to the center-west, one-sixteenth section corner of section 19;
153. thence northerly, a distance of approximately 0.25 miles, on the north and south center line of the northwest one-quarter of section 19, T. 10 N., R. 64 E., to the northwest one-sixteenth section corner of section 19;
154. thence westerly, a distance of approximately 0.25 miles, on the

- east and west center line of the northwest one-quarter of section 19, T. 10 N., R. 64 E., to the north one-sixteenth section corner of sections 19 and 24, on the west boundary of T. 10 N., R. 64 E.;
155. thence westerly, a distance of approximately 20 feet, on the east and west center line of the northeast one-quarter of section 24, T. 10 N., R. 63 E., to intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of the aforementioned improved road, described in course No. 148, bears northwesterly and southerly, at approximate latitude $38^{\circ}42'54''$ North, longitude $114^{\circ}50'32''$ West;
156. thence northwesterly turning northerly, a distance of approximately 0.45 miles, on a line parallel with and 100 feet northeasterly and easterly of the northeasterly and easterly edge of the improved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of a jeep trail, bears northeasterly and southwesterly, at observed latitude $38^{\circ}43'14.616''$ North, longitude $114^{\circ}50'42.495''$ West;
157. thence northeasterly, a distance of approximately 2.3 miles, on a line parallel with and 100 feet southeasterly of the southeasterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, at observed latitude $38^{\circ}44'15.924''$ North, longitude $114^{\circ}48'55.792''$ West;
158. thence N. $65^{\circ}53'30''$ W., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of the jeep trail, at observed latitude $38^{\circ}44'16.771''$ North, longitude $114^{\circ}48'58.211''$ West;
159. thence southwesterly, a distance of approximately 2.2 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of aforementioned improved road, described in course No. 156, bears northerly and southerly, at observed latitude $38^{\circ}43'17.675''$ North, longitude $114^{\circ}50'40.869''$ West;
160. thence northerly, a distance of approximately 2.8 miles, on a line parallel with and 100 feet easterly of the easterly edge of

- the improved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 38°45'32.520" North, longitude 114°50'00.464" West;
161. thence S. 77°26'50" E., a distance of 455.7 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with a collar of stone, 2 feet base, to top, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°45'31.542" North, longitude 114°49'54.851" West;
162. thence N. 3°45'20" E., a distance of 359.5 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at observed latitude 38°45'35.087" North, longitude 114°49'54.553" West;
163. thence N. 76°52'10" W., a distance of 418.8 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of aforementioned improved road, described in course No. 160, at observed latitude 38°45'36.026" North, longitude 114°49'59.700" West;
164. thence northerly turning northeasterly, a distance of approximately 0.9 miles, on a line parallel with and 100 feet easterly and southeasterly of the easterly and southeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked MGW N83916 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southerly of the southerly edge of an unimproved road, bears easterly and westerly, at observed latitude 38°46'18.618" North, longitude 114°49'54.977" West;
165. thence easterly turning southerly, a distance of approximately 3.1 miles, on a line parallel with and 100 feet southerly and westerly of the southerly and westerly edge of the unimproved road to intersection with the east and west center line of section 33, T. 11 N., R. 64 E., at approximate latitude 38°46'18" North, longitude 114°46'53" West;
166. thence westerly, a distance of approximately 0.25 miles, on the east and west center line of section 33, T. 11 N., R. 64 E., to the center-east, one-sixteenth section corner of section 33;
167. thence southerly, a distance of approximately 0.25 miles, on the north and south center line of the southeast one-quarter of section 33, T. 11 N., R. 64 E., to the southeast one-sixteenth section corner of section 33;

168. thence easterly, a distance of approximately 0.25 miles, on the east and west center line of the southeast one-quarter of section 33, T. 11 N., R. 64 E., to the south one-sixteenth section corner of sections 33 and 34;
169. thence northerly, a distance of approximately 0.15 miles, on the line between sections 33 and 34, T. 11 N., R. 64 E., to intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of the aforementioned unimproved road, described in course No. 165, bears easterly and westerly, at approximate latitude $38^{\circ}46'12''$ North, longitude $114^{\circ}46'53''$ West;
170. thence easterly turning northerly and westerly, a distance of approximately 3.2 miles, on a line parallel with and 100 feet southerly, easterly, and northerly of the southerly, easterly, and northerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of aforementioned improved road, described in course No. 165 bears northeasterly and southwesterly, at observed latitude $38^{\circ}46'20.454''$ North, longitude $114^{\circ}49'53.722''$ West;
171. thence northeasterly, a distance of approximately 0.75 miles, on a line parallel with and 100 feet southeasterly of the southeasterly edge of aforementioned improved road, described in course No. 164, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, on said line, at observed latitude $38^{\circ}46'54.214''$ North, longitude $114^{\circ}49'33.011''$ West;
172. thence S. $22^{\circ}26'40''$ E., a distance of 463.5 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with a collar of stone, at observed latitude $38^{\circ}46'49.981''$ North, longitude $114^{\circ}49'30.777''$ West;
173. thence N. $45^{\circ}52'50''$ E., a distance of 486.7 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, at observed latitude $38^{\circ}46'53.329''$ North, longitude $114^{\circ}49'26.366''$ West;
174. thence N. $49^{\circ}52'00''$ W., a distance of 471.6 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of aforementioned improved road, described in course No. 171, at observed latitude $38^{\circ}46'56.333''$ North, longitude $114^{\circ}49'30.918''$ West;
175. thence northeasterly turning northerly, a distance of approximately 5.2 miles, on a line parallel with and 100 feet southeasterly and easterly of the southeasterly and easterly edge of unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, at intersection with the line between

sections 6 and 31, on the north boundary of T. 11 N., R. 64 E., at observed latitude 38°51'01.907" North, longitude 114°49'14.777" West.

From this point, the one-quarter section corner of sections 6 and 31, on the north boundary of T. 11 N., R. 64 E., bears N. 87°07'00" W., 1,973.2 feet, monumented with an iron post, 2 1/2 inches diameter, firmly set, projecting 5 inches above the ground, with brass cap marked T12N R64E 1/4 S31 S6 T11N 1964, and in a mound of stone, 3 feet diameter, 6 inches high, northerly of the corner.

176. From the end of course No. 175, thence S. 87°07'00" E., a distance of 585.3 feet, on the line between sections 6 and 31, on the north boundary of T. 11 N., R. 64 E., to the corner of sections 5, 6, 31, and 32, and the Point of Beginning.

Excepting from herein the southwest one-quarter of the northwest one-quarter of section 10, the southeast one-quarter of the southeast one-quarter of section 22, the southeast one-quarter of the southwest one-quarter of section 27, and the east one-half of the southeast one-quarter of section 34, T. 10 N., R. 64 E.

Also excepting from herein Lots 1 and 2 of section 4, T. 9 N., R. 64 E.

The area contained within the bounds of this description is 78,730 acres, more or less.

Pursuant to Section 324(c) of Public Law No. 109-432, the inholdings excepted from the area described above shall become part of this wilderness designation if acquired by the United States.

END OF DESCRIPTION

The acreage noted in the description is based on a GIS polygon projected onto the 1983 North American Datum Universal Transverse Mercator projection, zone 11.

The direction of each line is with reference to the true meridian.

The geographic positions noted as "approximate" latitude and longitude are referenced to the North American Datum of 1983 and were digitized from the following editions of the United States Geologic Survey 7.5 minute quadrangle maps. The elevations noted are referenced to sea level and are taken from these same maps.

Bullwhack Summit, Nev., 1977
Cattle Camp Spring, Nev., 1973
Parker Station, Nev., 1969
Mount Grafton, Nev., 1978
Shingle Pass SE, Nev., 1969
Milk Ranch Spring, Nev., 1978

The geographic positions noted as "observed" latitude and longitude are referenced to the North American Datum of 1983. Observed positions were determined in 2012 and 2013 utilizing Global Positioning System (GPS), Real Time Kinematic (RTK) observations. All RTK observations were carried forward from local control established using GPS static observations processed with the National Geodetic Survey Online Positioning User Service (OPUS) referenced to the following Continuously Operating Reference Stations (CORS): "EGAN EGAN BRGN NV1996 CORS ARP", "GOSH GOSH BRGN UT1996 CORS ARP" "NVPI PIOCHE CORS ARP", "ST GEORGE PUTIL CORS ARP", "PIOCHE CORS ARP", "MARYSVALE UT2006 CORS ARP", "SALT LAKE CITY CORS ARP", and "SPRING VALLEY CORS ARP", and carried forward by Real Time Kinematic (RTK) observations in 2013 and 2014.

WILDERNESS AREA
Mount Grafton Wilderness
Bureau of Land Management

I hereby certify that the maps and legal boundary description herewith represents the boundary of the Mount Grafton Wilderness within the jurisdiction of the Ely District Office, Nevada, Bureau of Land Management.

Signed: _____ Date: _____
Chief, Branch of Geographic Sciences
Bureau of Land Management, Nevada

I hereby certify and accept the maps and legal boundary description of Mount Grafton Wilderness within the Ely District Office, Nevada, Bureau of Land Management, as entered into the Wilderness System under the "White Pine County Conservation, Recreation, and Development Act of 2006", Public Law No. 109-432.

Signed: _____ Date: _____
State Director, Nevada
Bureau of Land Management